

# Coming Soon



**Order Code**  
**Commander-1**



**Order Code**  
**Commander-2**



## TECHNICAL DATA

<b>Microphone:</b>	
Directivity:	Unidirectional
Impedance:	1.0kΩ
Sensitivity:	-49±3dB (0dB=1V/Pa)
Frequency Range:	100-16,000Hz
Operating Temp:	-20°C~+60°C
Storage Temp:	-25°C~+70°C
<b>Speaker:</b>	
Size:	ø30 mm
Input Power:	50 mW (1.26V)
Max Power:	100 mW (1.79V)
Impedance:	32Ω ±10% at 1kHz, 0.18V
Sound Pressure:	122±3dB at 1kHz
Resonance Frequency:	150±30 (20%) Hz
Frequency Range:	20Hz ~ 20,000Hz
Operating Temp:	-25°C ~ +50°C
Storage Temp:	-25°C ~ +50°C



USB-A



LEATHERETTE CUSHION



## Commander

Universal 'Plug & play' USB professional office and contact centre headset, compatible with all major softphones. Fitted with 60mm leatherette ear cushions and padded T-bar, suitable for regular phone users.

### Overview

Features	Single or dual speakers
	Left / right speaker side compatible
	Stereo audio sound for music and mono audio for speech
	Surround Shield™ noise cancelling microphone
	Fully flexible microphone for exact positioning
	270° adjustable microphone boom
	'Put and stay' ratchet microphone boom arm
	Swivel T-bar with padded leatherette cushion
	Overhead, padded sure-fit fully adjustable headband
What's included	Headset fitted with 60mm leatherette ear cushions and supplied with Quick Start Guide
Headset Weight	~ 54g / ~ 80g
Connection	USB-A direct plug-in
Certifications	FCC, CE, RoHS, REACH
Warranty	2 Years repair or replacement warranty
MOQ	Master Shipping Carton: 60
EAN:	Commander-1: 5060126958659, Commander-2: 5060126958673
SKU:	Commander-1: 575-344-001, Commander-2: 575-344-002

### In-line Control Features

- 3 button in-line control with volume and mute
- 'Plug & Play' solution - No software download needed
- User will know the buttons by feel as each button will feel different
- Ribbing on the side of the control box to indicate the direction of the buttons
- LED illumination for power and in-use

