

# KODAK Access Webcam

WINDOWS HELLO COMPATIBLE



## Office security using facial recognition

### Features

The KODAK Access Webcam is the perfect solution for ensuring office security with its Windows Hello facial recognition sensor. With this feature, you can be confident that your device is secure and accessible only to authorised personnel.

The KODAK Access Webcam also packs in all the features you need. Full HD video quality, omnidirectional microphone and "camera in-use" LED indicators. The KODAK Access Webcam comes with a built-in privacy lens cover, giving you peace of mind that you are hidden from view whilst the lens cover is pulled over the lens.

Plug and Play is also a great feature of the KODAK Access Webcam, with both USB-A and USB-C connection options, allowing you to plug in and start working immediately with many of the common video conferencing platforms including Microsoft® Teams, Zoom®, Google Meet, Cisco Webex and many more.

- HD 1920 x 1080p CMOS Camera
- Full HD 1080p glass lens
- Built-in privacy lens cover
- Omnidirectional microphone
- Built-in camera in-use LED indicator
- USB Type-A and USB-C connectivity
- Desk / monitor mount and universal thread for tripod option
- Full 360° camera rotation and 90° tilt for over desk viewing
- Automatic low-light correction
- AEC – Automatic Echo Cancellation
- ANS – Automatic Noise Suppression



Available Colors:

● Black



# KODAK Access Webcam

WINDOWS HELLO COMPATIBLE

## SPECIFICATIONS

IR Camera SENSOR: Sensor Type 1/9"CMOS Array Size Pixel Size	1280*720 30FPS 1.4µm x 1.4µm / BSI
RGB Camera SENSOR: Sensor Type Array Size Pixel Size	1/2.9" CMOS 1920*1080P 30FPS 2.8µm*2.8µm FSI
IR Lens: Construction IR Filter FOV F/No TV Distortion	3P 850nm D=85±°; 2.4±5% <-2.6%
RGB Lens: Construction IR Filter FOV F/No TV Distortion	1G4P+IR 650nm D=96±° 2.5±5% <-0.9%
MIC: Dimensional Sensitivity S/N ratio Pick-up distance	Ø4.0*1.5mm -38±3db 60db 3m
Temperature (Operation)	-10°c to 60°c
Temperature (Storage)	-10°c to 60°c
USB Power Supply Voltage	DC 5V
Interface	USB 2.0 USB-A/TYPE-C
Operating System (Common Camera)	Windows® 8 and above / Linux / Mac
Operating System (Windows Hello)	Windows® 10-11
AGE/AEC/White Balance	Auto
Supports Compression Formats	MJPEG/YUV
Certifications	UKCA, CE, FCC, RoHS, REACH
Country of Origin	Taiwan
Unit Dimensions	92.5 x 52 x 31 mm
Warranty	3 Years Limited Warranty – includes 2 years standard no quibble repair or replace warranty PLUS a 3rd year cover on all non-moving parts
SKU:	575-432-001
EAN:	5060969680878

[www.jpltele.com/kodak/kodak-access-webcam](http://www.jpltele.com/kodak/kodak-access-webcam)

© 2023 JPL Telecom Ltd. All rights reserved.

Made in Taiwan

The Kodak trademark, logo, and trade dress are used under license from Kodak.

**UK Office:** JPL Telecom Ltd.  
Church Close, Todber, Sturminster Newton, Dorset, DT10 1JH, England

**USA Office:** JPL Telecom LLC.  
445 W Merritt Avenue, Merritt Island, FL 32953, USA

**EU Office:** JPL Telecom B.V.  
John M. Keynesplein 10, 1066 EP Amsterdam, NETHERLANDS

All information contained in this document is subject to change without notice.

E&OE 08/23/432 EN

